

## Technische Daten SMS-120/30-60/...

Artikelnummer Typ	Breite mm	Länge mm	Gewicht kg	Sauggummi Design	ScrewOn	Snap On	Ejektor intern	Ejektor extern	Reversierung intern	Reversierung extern	Befestigung	Abhebungskraft in N bei 100% Belegung		Luftverbrauch NL/min (bei 6 bar)
												40% Vakuum	80% Vakuum	
300030210 SMS-120/30/20/10	122	30	0,2	E	-	-	-	-	-	-	2x M6	27	54	-
300045210 SMS-120/45/20/15	122	49	0,35	E	-	<b>X</b>	-	-	-	-	2x M6	54	108	-
300060110 SMS-120/60/15.20/15	122	64	0,45	D	-	<b>X</b>	-	-	-	-	4x M6	36	72	-
300060210 SMS-120/60/20/15	122	64	0,45	E	-	<b>X</b>	-	-	-	-	4x M6	54	108	-

### Ersatzteile:

Typ	ScrewOn- (Schnellwechsel-) Platte	Sauggummi
SMS-120/30/20/...	320090212	330030212
SMS-120/45/20/...	320120212	330045212
SMS-120/60/15.20/...	320060112	330060112
SMS-120/60/20/...	320060212	330060212

## Technische Daten SMS-120/90... & SMS-120/120...

Artikelnummer Typ	Breite mm	Länge mm	Gewicht kg	Sauggummi Design	ScrewOn	Snap On	Ejektor intern	Ejektor extern	Reversierung intern	Reversierung extern	Befestigung	Abhebungskraft in N bei 100% Belegung		Luftverbrauch NL/min (bei 6 bar)
												40% Vakuum	80% Vakuum	
300090110 SMS-120/90/15.20/15	122	94	0,6	D	-	<b>X</b>	-	-	-	-	4x M6	72	144	-
300090210 SMS-120/90/20/15	122	94	0,6	E	-	<b>X</b>	-	-	-	-	4x M6	108	216	-
300120110 SMS-120/120/15.20/15	122	124	0,75	D	<b>X</b>	-	-	-	-	-	4x M6	112	224	-
300120210 SMS-120/120/20/15	122	124	0,75	E	<b>X</b>	-	-	-	-	-	4x M6	135	270	-

### Zubehör:

Typ	Vakuum - Steuerventil	Reversierungs - Steuerventil
SMS-120/90/.../15	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38
SMS-120/120/.../15	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38

### Ersatzteile:

Typ	ScrewOn- (Schnellwechsel-) Platte	Sauggummi
SMS-120/90/15.20/...	320090112	330090112
SMS-120/90/20/...	320090212	330090212
SMS-120/120/15.20/...	320120112	330120112
SMS-120/120/20/...	320120212	330120212

## Technische Daten SMS-120/200...

Artikelnummer Typ	Breite mm	Länge mm	Gewicht kg	Sauggummi Design	ScrewOn	Snap On	Ejektor intern	Ejektor extern	Reversierung intern	Reversierung extern	Befestigung	Abhebungskraft in N bei 100% Belegung		Luftverbrauch NL/min (bei 6 bar)
												40% Vakuum	80% Vakuum	
300200110 SMS-120/200/15.20/20	126	206	1,3	D	X	-	-	-	-	-	4x M8	139	278	-
300200111 SMS-120/200/15.20/20-ER	126	206	2,3	D	X	-	-	X	X	-	4x M8	139	278	210
300200112 SMS-120/200/15.20/20-E	126	206	2,2	D	X	-	-	X	-	X	4x M8	139	278	210
300200210 SMS-120/200/20/20	126	206	1,3	E	X	-	-	-	-	-	4x M8	189	378	-
300200211 SMS-120/200/20/20-ER	126	206	2,3	E	X	-	-	X	X	-	4x M8	189	378	210
300200212 SMS-120/200/20/20-E	126	206	2,2	E	X	-	-	X	-	X	4x M8	189	378	210
300200310 SMS-120/200/30/20	126	206	1,3	F	X	-	-	-	-	-	4x M8	231	462	-
300200311 SMS-120/200/30/20-ER	126	206	2,3	F	X	-	-	X	X	-	4x M8	231	462	105
300200312 SMS-120/200/30/20-E	126	206	2,2	F	X	-	-	X	-	X	4x M8	231	462	105

### Zubehör:

Typ	Vakuum - Steuerventil	Reversierungs - Steuerventil
SMS-120/200/.../20	2/2-Wege Sitzventil, G1", 24 V/DC VNA10006-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38
SMS-120/200/.../20-ER	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2	5/2-Wege Magnetventil, G1/8", 24 V/DC UG RBV 18
SMS-120/200/.../20-E	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38

### Ersatzteile:

Typ	ScrewOn- (Schnellwechsel-) Platte	Sauggummi
SMS-120/200/15.20/...	320200112	330200112
SMS-120/200/20/...	320200212	330200212
SMS-120/200/30/...	320200312	330200312

## Technische Daten SMS-120/300...

Artikelnummer Typ	Breite mm	Länge mm	Gewicht kg	Sauggummi Design	ScrewOn	Snap On	Ejektor intern	Ejektor extern	Reversierung intern	Reversierung extern	Befestigung	Abhebungskraft in N bei 100% Belegung		Luftverbrauch NL/min (bei 6 bar)
												40% Vakuum	80% Vakuum	
300300110 SMS-120/300/15.20/20	126	306	2	D	X	-	-	-	-	-	4x M8	217	434	-
300300111 SMS-120/300/15.20/20-ER	126	306	3	D	X	-	X	-	X	-	4x M8	217	434	420
300300112 SMS-120/300/15.20/20-E	126	306	2,9	D	X	-	X	-	-	X	4x M8	217	434	420
300300210 SMS-120/300/20/20	126	306	2	E	X	-	-	-	-	-	4x M8	380	760	-
300300211 SMS-120/300/20/20-ER	126	306	3	E	X	-	X	-	X	-	4x M8	380	760	315
300300212 SMS-120/300/20/20-E	126	306	2,9	E	X	-	X	-	-	X	4x M8	380	760	315
300300310 SMS-120/300/30/20	126	306	1,9	F	X	-	-	-	-	-	4x M8	370	740	-
300300311 SMS-120/300/30/20-ER	126	306	2,9	F	X	-	X	-	X	-	4x M8	370	740	210
300300312 SMS-120/300/30/20-E	126	306	2,8	F	X	-	X	-	-	X	4x M8	370	740	210

### Zubehör:

Typ	Vakuum - Steuerventil	Reversierungs - Steuerventil
SMS-120/300/.../20	2/2-Wege Sitzventil, G1", 24 V/DC VNA10006-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38
SMS-120/300/.../20-ER	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2	5/2-Wege Magnetventil, G1/8", 24 V/DC UG RBV 18
SMS-120/300/.../20-E	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38

### Ersatzteile:

Typ	ScrewOn- (Schnellwechsel-) Platte	Sauggummi
SMS-120/300/15.20/...	320300112	330300112
SMS-120/300/20/...	320300212	330300212
SMS-120/300/30/...	320300312	330300312

## Technische Daten SMS-120/400...

Artikelnummer Typ	Breite mm	Länge mm	Gewicht kg	Sauggummi Design	ScrewOn	Snap On	Ejektor intern	Ejektor extern	Reversierung intern	Reversierung extern	Befestigung	Abhebungskraft in N bei 100% Belegung		Luftverbrauch NL/min (bei 6 bar)
												40% Vakuum	80% Vakuum	
300400110 SMS-120/400/15.20/20	126	406	2,5	D	X	-	-	-	-	-	4x M8	300	600	-
300400111 SMS-120/400/15.20/20-ER	126	406	3,5	D	X	-	X	-	X	-	4x M8	300	600	420
300400112 SMS-120/400/15.20/20-E	126	406	3,4	D	X	-	X	-	-	X	4x M8	300	600	420
300400210 SMS-120/400/20/20	126	406	2,5	E	X	-	-	-	-	-	4x M8	300	600	-
300400211 SMS-120/400/20/20-ER	126	406	3,5	E	X	-	X	-	X	-	4x M8	510	1020	420
300400212 SMS-120/400/20/20-E	126	406	3,4	E	X	-	X	-	-	X	4x M8	510	1020	420
300400310 SMS-120/400/30/20	126	406	2,4	F	X	-	-	-	-	-	4x M8	500	1000	-
300400311 SMS-120/400/30/20-ER	126	406	3,4	F	X	-	X	-	X	-	4x M8	500	1000	210
300400312 SMS-120/400/30/20-E	126	406	3,3	F	X	-	X	-	-	X	4x M8	500	1000	210

### Zubehör:

Typ	Vakuum - Steuerventil	Reversierungs - Steuerventil
SMS-120/400/.../20	2/2-Wege Sitzventil, G1", 24 V/DC VNA10006-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38
SMS-120/400/.../20-ER	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2	5/2-Wege Magnetventil, G1/8", 24 V/DC UG RBV 18
SMS-120/400/.../20-E	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38

### Ersatzteile:

Typ	ScrewOn- (Schnellwechsel-) Platte	Sauggummi
SMS-120/400/15.20/...	320400112	330400112
SMS-120/400/20/...	320400212	330400212
SMS-120/400/30/...	320400312	330400312

## Technische Daten SMS-120/600...

Artikelnummer Typ	Breite mm	Länge mm	Gewicht kg	Sauggummi Design	ScrewOn	Snap On	Ejektor intern	Ejektor extern	Reversierung intern	Reversierung extern	Befestigung	Abhebungskraft in N bei 100% Belegung		Luftverbrauch NL/min (bei 6 bar)
												40% Vakuum	80% Vakuum	
300600110 SMS-120/600/15.20/20	126	606	3,6	D	X	-	-	-	-	-	8x M8	456	912	-
300600111 SMS-120/600/15.20/20-ER	126	606	5,6	D	X	-	X	-	X	-	8x M8	456	912	735
300600112 SMS-120/600/15.20/20-E	126	606	5,5	D	X	-	X	-	-	X	8x M8	456	912	735
300600210 SMS-120/600/20/20	126	606	3,6	E	X	-	-	-	-	-	8x M8	785	1570	-
300600211 SMS-120/600/20/20-ER	126	606	4,6	E	X	-	X	-	X	-	8x M8	785	1570	420
300600212 SMS-120/600/20/20-E	126	606	4,5	E	X	-	X	-	-	X	8x M8	785	1570	420
300600310 SMS-120/600/30/20	126	606	3,5	F	X	-	-	-	-	-	8x M8	730	1460	-
300600311 SMS-120/600/30/20-ER	126	606	4,5	F	X	-	X	-	X	-	8x M8	730	1460	315
300600312 SMS-120/600/30/20-E	126	606	4,4	F	X	-	X	-	-	X	8x M8	730	1460	315

### Zubehör:

Typ	Vakuum - Steuerventil	Reversierungs - Steuerventil
SMS-120/600/.../20	2/2-Wege Sitzventil, G1", 24 V/DC VNA10006-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38
SMS-120/600/.../20-ER	2/2-Wege Sitzventil, G1/2", 24 V/DC VNC10004-M2	5/2-Wege Magnetventil, G1/8", 24 V/DC UG RBV 18
SMS-120/600/.../20-E	2/2-Wege Sitzventil, G1/2", 24 V/DC VNC10004-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38

### Ersatzteile:

Typ	ScrewOn- (Schnellwechsel-) Platte	Sauggummi
SMS-120/600/15.20/...	320600112	330600112
SMS-120/600/20/...	320600212	330600212
SMS-120/600/30/...	320600312	330600312

## Technische Daten SMS-120/800...

Artikelnummer Typ	Breite mm	Länge mm	Gewicht kg	Sauggummi Design	ScrewOn	Snap On	Ejektor intern	Ejektor extern	Reversierung intern	Reversierung extern	Befestigung	Abhebungskraft in N bei 100% Belegung		Luftverbrauch NL/min (bei 6 bar)
												40% Vakuum	80% Vakuum	
300800110 SMS-120/800/15.20/20	126	806	4,8	D	X	-	-	-	-	-	8x M8	618	1236	-
300800111 SMS-120/800/15.20/20-ER	126	806	6,8	D	X	-	X	-	X	-	8x M8	618	1236	840
300800112 SMS-120/800/15.20/20-E	126	806	6,6	D	X	-	X	-	-	X	8x M8	618	1236	840
300800210 SMS-120/800/20/20	126	806	4,8	E	X	-	-	-	-	-	8x M8	1050	2100	-
300800211 SMS-120/800/20/20-ER	126	806	6,8	E	X	-	X	-	X	-	8x M8	1050	2100	840
300800212 SMS-120/800/20/20-E	126	806	6,6	E	X	-	X	-	-	X	8x M8	1050	2100	840
300800310 SMS-120/800/30/20	126	806	4,8	F	X	-	-	-	-	-	8x M8	982	1964	-
300800311 SMS-120/800/30/20-ER	126	806	5,8	F	X	-	X	-	X	-	8x M8	982	1964	420
300800312 SMS-120/800/30/20-E	126	806	5,7	F	X	-	X	-	-	X	8x M8	982	1964	420

### Zubehör:

Typ	Vakuum - Steuerventil	Reversierungs - Steuerventil
SMS-120/800/.../20	2/2-Wege Sitzventil, G1-1/2", 24 V/DC VNA10008-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38
SMS-120/800/.../20-ER	2/2-Wege Sitzventil, G1/2", 24 V/DC VNC10004-M2	5/2-Wege Magnetventil, G1/8", 24 V/DC UG RBV 18
SMS-120/800/.../20-E	2/2-Wege Sitzventil, G1/2", 24 V/DC VNC10004-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38

### Ersatzteile:

Typ	ScrewOn- (Schnellwechsel-) Platte	Sauggummi
SMS-120/800/15.20/...	320800112	330800112
SMS-120/800/20/...	320800212	330800212
SMS-120/800/30/...	320800312	330800312

## Technische Daten SMS-120/1000...

Artikelnummer Typ	Breite mm	Länge mm	Gewicht kg	Sauggummi Design	ScrewOn	Snap On	Ejektor intern	Ejektor extern	Reversierung intern	Reversierung extern	Befestigung	Abhebungskraft in N bei 100% Belegung		Luftverbrauch NL/min (bei 6 bar)
												40% Vakuum	80% Vakuum	
300800110 SMS-120/800/15.20/20	126	806	4,8	D	X	-	-	-	-	-	8x M8	618	1236	-
300800111 SMS-120/800/15.20/20-ER	126	806	6,8	D	X	-	X	-	X	-	8x M8	618	1236	840
300800112 SMS-120/800/15.20/20-E	126	806	6,6	D	X	-	X	-	-	X	8x M8	618	1236	840
300800210 SMS-120/800/20/20	126	806	4,8	E	X	-	-	-	-	-	8x M8	1050	2100	-
300800211 SMS-120/800/20/20-ER	126	806	6,8	E	X	-	X	-	X	-	8x M8	1050	2100	840
300800212 SMS-120/800/20/20-E	126	806	6,6	E	X	-	X	-	-	X	8x M8	1050	2100	840
300800310 SMS-120/800/30/20	126	806	4,8	F	X	-	-	-	-	-	8x M8	982	1964	-
300800311 SMS-120/800/30/20-ER	126	806	5,8	F	X	-	X	-	X	-	8x M8	982	1964	420
300800312 SMS-120/800/30/20-E	126	806	5,7	F	X	-	X	-	-	X	8x M8	982	1964	420

### Zubehör:

Typ	Vakuum - Steuerventil	Reversierungs - Steuerventil
SMS-120/800/.../20	2/2-Wege Sitzventil, G1-1/2", 24 V/DC VNA10008-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38
SMS-120/800/.../20-ER	2/2-Wege Sitzventil, G1/2", 24 V/DC VNC10004-M2	5/2-Wege Magnetventil, G1/8", 24 V/DC UG RBV 18
SMS-120/800/.../20-E	2/2-Wege Sitzventil, G1/2", 24 V/DC VNC10004-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC UG RBV extern 38

### Ersatzteile:

Typ	ScrewOn- (Schnellwechsel-) Platte	Sauggummi
SMS-120/800/15.20/...	320800112	330800112
SMS-120/800/20/...	320800212	330800212
SMS-120/800/30/...	320800312	330800312



## Technische Daten SMS-120/1200...

Artikelnummer Typ	Breite mm	Länge mm	Gewicht kg	Sauggummi Design	ScrewOn	Snap On	Ejektor intern	Ejektor extern	Reversierung intern	Reversierung extern	Befestigung	Abhebungskraft in N bei 100% Belegung		Luftverbrauch NL/min (bei 6 bar)
												40% Vakuum	80% Vakuum	
301200110 SMS-120/1200/15.20/20	126	1206	8	D	X	-	-	-	-	-	12x M8	930	1860	-
301200111 SMS-120/1200/15.20/20-ER	126	1206	11	D	X	-	X	-	X	-	12x M8	930	1860	1680
301200112 SMS-120/1200/15.20/20-E	126	1206	10,7	D	X	-	X	-	-	X	12x M8	930	1860	1680
301200210 SMS-120/1200/20/20	126	1206	8	E	X	-	-	-	-	-	12x M8	1590	3180	-
301200211 SMS-120/1200/20/20-ER	126	1206	10	E	X	-	X	-	X	-	12x M8	1590	3180	1260
301200212 SMS-120/1200/20/20-E	126	1206	9,8	E	X	-	X	-	-	X	12x M8	1590	3180	1260
301200310 SMS-120/1200/30/20	126	1206	8	F	X	-	-	-	-	-	12x M8	1500	3000	-
301200311 SMS-120/1200/30/20-ER	126	1206	9	F	X	-	X	-	X	-	12x M8	1500	3000	840
301200312 SMS-120/1200/30/20-E	126	1206	8,9	F	X	-	X	-	-	X	12x M8	1500	3000	840

### Zubehör:

Typ	Vakuum - Steuerventil	Reversierungs - Steuerventil
SMS-120/1200/.../20	2/2-Wege Sitzventil, G2", 24 V/DC VNA10009-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2
SMS-120/1200/.../20-ER	2/2-Wege Sitzventil, G1", 24 V/DC VNC10006-M2	5/2-Wege Magnetventil, G1/8", 24 V/DC UG RBV 18
SMS-120/1200/.../20-E	2/2-Wege Sitzventil, G1", 24 V/DC VNC10006-M2	2/2-Wege Sitzventil, G3/8", 24 V/DC VNC10003-M2

### Ersatzteile:

Typ	ScrewOn- (Schnellwechsel-) Platte	Sauggummi
SMS-120/1200/15.20/...	321200112	331200112
SMS-120/1200/20/...	321200212	331200212
SMS-120/1200/30/...	321200312	331200312